NOROX®PD-40



Date of last issue: -Version Revision Date: SDS Number:

60000000160 Date of first issue: 15.05.2023 1.0 15.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

: NOROX®PD-40 Trade name

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-: Hardener

stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : United Initiators GmbH

Dr.-Gustav-Adolph-Str. 3

82049 Pullach

Telephone : +49 / 89 / 74422 - 0

E-mail address of person

responsible for the SDS

: contact@united-in.com

1.4 Emergency telephone number

+27 21 300 2732

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Organic peroxides, Type D H242: Heating may cause a fire.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Reproductive toxicity, Category 2 H361: Suspected of damaging fertility or the un-

born child.

Specific target organ toxicity - single ex-

posure, Category 3, Respiratory system

H335: May cause respiratory irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

Hazard pictograms :







Signal word : Danger

Hazard statements : H242 Heating may cause a fire.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

Precautionary statements :

Prevention:

P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials.

P233 Keep container tightly closed.

P235 Keep cool.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label: 3,5-dimethyl-1,2-dioxolane-3,5-diol (CAS-No. 13784-51-5) Diacetone alcohol (CAS-No. 123-42-2)

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Organic Peroxide

Liquid mixture

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
2,4-Pentanedione, peroxide	37187-22-7	Org. Perox. D;	>= 30 - < 50
	237-438-9	H242	
	01-2119965139-28-	Eye Irrit. 2; H319	
	0005	Skin Sens. 1; H317	
Diacetone alcohol	123-42-2	Eye Irrit. 2; H319	>= 30 - < 50
	204-626-7	Repr. 2; H361	
	603-016-00-1	STOT SE 3; H335	
	01-2119473975-21	(Respiratory sys-	
		tem)	
Acetylacetone	123-54-6	Flam. Liq. 3; H226	>= 1 - < 10
	204-634-0	Acute Tox. 4; H302	
	606-029-00-0	Acute Tox. 3; H331	
	01-2119458968-15	Acute Tox. 3; H311	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

Symptoms of poisoning may appear several hours later.

Call a physician immediately.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If inhaled : If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

If symptoms persist, call a physician.

If breathed in, move person into fresh air.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash contaminated clothing before re-use.

If on skin, rinse well with water.
If on clothes, remove clothes.
If symptoms persist, call a physician.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Call a physician immediately. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.

Causes serious eye irritation. May cause respiratory irritation.

Suspected of damaging fertility or the unborn child.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating de-

composition reaction with release of flammable vapors which

may auto-ignite.

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

The product burns violently.

Flash back possible over considerable distance. Vapours may form explosive mixtures with air.

Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary. Use personal protective equipment.

Specific extinguishing meth-

ods

Do not use a solid water stream as it may scatter and spread

fire

Remove undamaged containers from fire area if it is safe to do

SO.

Use water spray to cool unopened containers.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Remove all sources of ignition.

Follow safe handling advice and personal protective equip-

ment recommendations.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Never return spills in original containers for re-use.

Treat recovered material as described in the section "Disposal

considerations".

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contact with incompatible substances can cause decomposi-

tion at or below SADT. Clear spills immediately.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05,2023 60000000160 Date of first issue: 15.05,2023

To clean the floor and all objects contaminated by this materi-

al, use plenty of water.

Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Advice on safe handling : Do not swallow.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Avoid formation of aerosol.

Take precautionary measures against static discharges. Never return any product to the container from which it was

originally removed.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid confinement.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash thoroughly after handling.

For personal protection see section 8.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Protect from contamination.

Advice on protection against

fire and explosion

Keep away from heat and sources of ignition. Use only explosion-proof equipment. Keep away from combustible material.

Hygiene measures : Keep away from food and drink. When using do not eat or

drink. When using do not smoke. Wash hands before breaks

and immediately after handling the product.

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Electrical installations / working materials must comply with the technological safety standards. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Store in accordance

with the particular national regulations.

Advice on common storage : Keep away from strong acids, bases, heavy metal salts and

other reducing substances.

Recommended storage tem- :

perature

10 - 25 °C

Further information on stor-

age stability

No decomposition if stored normally.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data

sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Diagotono algobal	100 10 0		FO 222	ZA OEL
Diacetone alcohol	123-42-2	OEL-RL	50 ppm	ZA OEL
			240 mg/m3	
	Further information: Occupational Exposure Limits - Restricted Limits For			
	Hazardous Chemical Agents			
		OEL- RL STEL/C	75 ppm	ZA OEL
			360 mg/m3	
	Further information: Occupational Exposure Limits - Restricted Limits For			
	Hazardous Chemical Agents			
Diacetone alcohol	123-42-2	OEL-RL	50 ppm	ZA OEL
			240 mg/m3	
	Further information: Occupational Exposure Limits - Restricted Limits For			
	Hazardous Chemical Agents			
		OEL- RL STEL/C	75 ppm	ZA OEL
			360 mg/m3	
	Further information: Occupational Exposure Limits - Restricted Limits For			
	Hazardous Chemical Agents			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

Substance name	End Use	Exposure routes	Potential health effects	Value
3,5-dimethyl-1,2- dioxolane-3,5-diol	Workers	Inhalation	Long-term systemic effects	11,75 mg/m3
	Workers	Skin contact	Long-term systemic effects	13,33 mg/kg bw/day
Diacetone alcohol	Workers	Inhalation	Acute local effects	240 mg/m3
	Workers	Skin contact	Long-term systemic effects	9,4 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	66,4 mg/m3
	Workers	Inhalation	Long-term local ef- fects	66,4 mg/m3
Acetylacetone	Workers	Inhalation		84 mg/m3
	Workers	Skin contact		12 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
3,5-dimethyl-1,2-dioxolane-3,5-diol	Fresh water	0,054 mg/l
	Marine water	0,0054 mg/l
	Intermittent use/release	0,054 mg/l
	Fresh water sediment	0,48 mg/kg
	Marine sediment	0,048 mg/kg
	Sewage treatment plant	6,2 mg/l
	Soil	0,065 mg/kg
Diacetone alcohol	Fresh water	2 mg/l
	Marine water	0,2 mg/l
	Sewage treatment plant	82 mg/l
	Fresh water sediment	9,06 mg/kg dry
		weight (d.w.)
	Marine sediment	0,91 mg/kg dry
		weight (d.w.)
	Soil	0,63 mg/kg dry
		weight (d.w.)
Acetylacetone	Fresh water	0,026 mg/l
	Marine water	0,0026 mg/l
	Sewage treatment plant	1,32 mg/l
	Fresh water sediment	0,155 mg/kg wet
		weight
	Marine sediment	0,0155 mg/kg
		wet weight
	Soil	0,01582 mg/kg
		wet weight

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05,2023 60000000160 Date of first issue: 15.05,2023

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face pro-

tection if there is a splash hazard.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Please follow all applicable local/national requirements when

selecting protective measures for a specific workplace.

Hand protection

Material : Nitrile rubber
Break through time : < 30 min
Glove thickness : 0,40 mm

Material : butyl-rubber
Break through time : 480 min
Glove thickness : 0,47 mm

Remarks : The data about break through time/strength of material are

standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of

workday.

Skin and body protection : Select appropriate protective clothing based on chemical re-

sistance data and an assessment of the local exposure poten-

tial.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable

suits) to avoid exposed skin surfaces.

Wear as appropriate:

Flame retardant antistatic protective clothing.

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.

Filter type : ABEK-filter

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : light yellow

Odour : slight

Odour Threshold : not determined

pH : No data available

Melting point/range : No data available

Boiling point/boiling range : No data available

Flash point : 68 °C

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit / Upper

flammability limit

Upper explosion limit

6,9 %(V)

(for a component of this mixture)

Lower explosion limit / Lower

flammability limit

Lower explosion limit

1,8 %(V)

(for a component of this mixture)

Vapour pressure : not determined

Relative vapour density : No data available

Relative density : not determined

Density : ca. 1,1 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Viscosity

Viscosity, dynamic : ca. 38 mPa.s

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

Viscosity, kinematic : not determined

Explosive properties : Not explosive

In use, may form flammable/explosive vapour-air mixture.

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Organic peroxide

9.2 Other information

Self-Accelerating decomposi-

tion temperature (SADT)

60 °C

Method: UN-Test H.4

SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Flammability (liquids) : Organic peroxide

Self-heating substances : The substance or mixture is not classified as self heating.

Self-ignition : The substance or mixture is not classified as pyrophoric.

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Protect from contamination.

Contact with incompatible substances can cause decomposi-

tion at or below SADT. Heat, flames and sparks. Avoid confinement.

10.5 Incompatible materials

Materials to avoid : Accelerators, strong acids and bases, heavy metals and

heavy metal salts, reducing agents

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

10.6 Hazardous decomposition products

Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Components:

3,5-dimethyl-1,2-dioxolane-3,5-diol:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male): > 13,1 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: Expert judgement

Assessment: The substance or mixture has no acute dermal

toxicity

Diacetone alcohol:

Acute oral toxicity : LD50 (Rat): 3.002 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC0 (Rat, male and female): >= 7,6 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 600000000160 Date of first issue: 15.05.2023

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD0 (Rat): > 1.875 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: No mortality observed at this dose.

Acetylacetone:

Acute oral toxicity : LD50 (Rat): 570 mg/kg

Acute toxicity estimate: 570 mg/kg Method: Calculation method

Acute inhalation toxicity : LC50 (Rat): 5,1 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Acute toxicity estimate: 5,1 mg/l Test atmosphere: vapour Method: Calculation method

Acute dermal toxicity : LD50 (Rabbit, female): 790 mg/kg

Acute toxicity estimate: 790 mg/kg Method: Calculation method

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:

2,4-Pentanedione, peroxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Diacetone alcohol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 600000000160 Date of first issue: 15.05.2023

Acetylacetone:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Components:

2,4-Pentanedione, peroxide:

Species : Rabbit

Method : OECD Test Guideline 405

Result : Eye irritation

Diacetone alcohol:

Species : Rabbit

Method : OECD Test Guideline 405

Result : Irritation to eyes, reversing within 21 days

Acetylacetone:

Species : Rabbit

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : Causes sensitisation.

Components:

2,4-Pentanedione, peroxide:

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : Probability or evidence of skin sensitisation in humans

Remarks : Causes sensitisation.

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

Diacetone alcohol:

Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Acetylacetone:

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:

2,4-Pentanedione, peroxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: positive

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse (male and female)
Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Diacetone alcohol:

Genotoxicity in vitro : Method: OECD Test Guideline 476

Result: negative

Method: OECD Test Guideline 471

Result: negative

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Remarks: Not classified due to data which are conclusive

although insufficient for classification.

Acetylacetone:

Genotoxicity in vitro : Method: OECD Test Guideline 471

NOROX®PD-40



Version 1.0

Revision Date: 15.05.2023

SDS Number: 600000000160

Date of last issue: -

Date of first issue: 15.05.2023

Result: negative

Method: OECD Test Guideline 479

Result: positive

Method: OECD Test Guideline 473

Result: positive

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Method: OECD Test Guideline 474

Result: positive

Method: OECD Test Guideline 483

Result: negative

Method: OECD Test Guideline 475

Result: negative

Method: OECD Test Guideline 478

Result: Equivocal

Test Type: DNA Repair

Species: Rat

Application Route: Oral

Result: negative

Species: Rat

Application Route: inhalation (vapour)

Method: OPPTS 870.5395

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

2,4-Pentanedione, peroxide:

Remarks : This information is not available.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

2,4-Pentanedione, peroxide:

Effects on fertility : Remarks: No data available

Effects on foetal develop: : Remarks: No data available

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

ment

Diacetone alcohol:

Effects on fertility : Species: Rat

Application Route: oral (gavage)

General Toxicity - Parent: NOAEL: 300 mg/kg body weight General Toxicity F1: NOAEL: 300 mg/kg body weight

Method: OECD Test Guideline 422

Effects on foetal develop-

ment

Species: Rat

Application Route: inhalation (vapour)
General Toxicity Maternal: NOAEL: 4,106
Embryo-foetal toxicity: NOAEL: 12.292
Method: OECD Test Guideline 414

Acetylacetone:

Effects on foetal develop-

ment

Species: Rat

Application Route: inhalation (vapour)
Duration of Single Treatment: 13 d
General Toxicity Maternal: NOAEC: 200
Teratogenicity: NOAEC Parent: 400
Embryo-foetal toxicity: NOAEC F1: 50
Method: OECD Test Guideline 414

Species: Rat

Application Route: inhalation (vapour)
Duration of Single Treatment: 13 d
General Toxicity Maternal: LOAEC: 400
Embryo-foetal toxicity: LOAEC F1: 200
Method: OECD Test Guideline 414

STOT - single exposure

May cause respiratory irritation.

Components:

Diacetone alcohol:

Target Organs : Respiratory system

Assessment : May cause respiratory irritation.

Not classified based on available information.

Repeated dose toxicity

Components:

Diacetone alcohol:

 Species
 : Rat

 NOAEL
 : 1,04 mg/l

 LOAEL
 : 4,685 mg/l

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

Application Route : inhalation (vapour)

Exposure time : 6 w

Method : OECD Test Guideline 412

Species : Rat

NOAEL : 100 mg/kg Application Route : oral (gavage)

Method : OECD Test Guideline 422

Acetylacetone:

Species : Rat

NOAEL : 200 mg/kg

LOAEL : 805 mg/kg

Application Pouts : inhelation (appli

Application Route : inhalation (vapour)

Exposure time : 9 d

Species : Rat NOAEL : 100 mg/kg

Application Route : inhalation (vapour)

Exposure time : 90 d

Method : OECD Test Guideline 413

Species : Rabbit
NOAEL : 244 mg/kg
LOAEL : 975 mg/kg
Application Route : Dermal
Exposure time : 9 d

Aspiration toxicity

Not classified based on available information.

Components:

Acetylacetone:

No aspiration toxicity classification

Further information

Product:

Remarks : No data available

Components:

2,4-Pentanedione, peroxide:

Remarks : No data available

Acetylacetone:

Remarks : Solvents may degrease the skin.

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,4-Pentanedione, peroxide:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 67,6 mg/l

Exposure time: 96 h
Test Type: semi-static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 7,05 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 5,36

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : 614 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Diacetone alcohol:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1.000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

: EbC50 (Pseudokirchneriella subcapitata (green algae)): >

1.000 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 1.000

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Acetylacetone:

Toxicity to fish : LC50 (Fish): 104 mg/l

Exposure time: 96 h

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 25,9 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 83,22

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 3,2

mg/I

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : 107,6 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

EC10: 13,2 mg/l Exposure time: 3 h

Method: OECD Test Guideline 209

Toxicity to fish (Chronic tox-

icity)

NOEC: 10 mg/l Exposure time: 34 d

Species: Pimephales promelas (fathead minnow)

Method: OECD Test Guideline 210

LOEC: 22 mg/l Exposure time: 34 d

Species: Pimephales promelas (fathead minnow)

Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOEC: 18 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Method: OECD Test Guideline 211

12.2 Persistence and degradability

Components:

2,4-Pentanedione, peroxide:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301D

Diacetone alcohol:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

Acetylacetone:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301C

12.3 Bioaccumulative potential

Components:

2,4-Pentanedione, peroxide:

Partition coefficient: n-

octanol/water

log Pow: 1,1 (25 °C)

Method: OECD Test Guideline 117

Diacetone alcohol:

Partition coefficient: n-

octanol/water

log Pow: -0,09 (20 °C)

Acetylacetone:

Bioaccumulation : Bioconcentration factor (BCF): 3,16

Remarks: Calculation

Partition coefficient: n-

octanol/water

log Pow: 0,68 (40 °C)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (VPVB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting poten-

tial

The substance/mixture does not contain components considered to have endocrine disrupting properties according to

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life.

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

Components:

2,4-Pentanedione, peroxide:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Dispose of in accordance with local regulations.

SECTION 14: Transport information

14.1 UN number

ADN : UN 3105
ADR : UN 3105
RID : UN 3105
IMDG : UN 3105
IATA : UN 3105

14.2 UN proper shipping name

ADN : ORGANIC PEROXIDE TYPE D, LIQUID

(ACETYL ACETONE PEROXIDE)

ADR : ORGANIC PEROXIDE TYPE D, LIQUID

(ACETYL ACETONE PEROXIDE)

RID : ORGANIC PEROXIDE TYPE D, LIQUID

(ACETYL ACETONE PEROXIDE)

IMDG : ORGANIC PEROXIDE TYPE D. LIQUID

(ACETYL ACETONE PEROXIDE)

IATA : Organic peroxide type D, liquid

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

(Acetyl acetone peroxide)

14.3 Transport hazard class(es)

ADN : 5.2
ADR : 5.2
RID : 5.2
IMDG : 5.2
IATA : 5.2

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : P1 Labels : 5.2

ADR

Packing group : Not assigned by regulation

Classification Code : P1 Labels : 5.2 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : P1 Hazard Identification Number : 539 Labels : 5.2

IMDG

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code : F-J, S-R

IATA (Cargo)

Packing instruction (cargo : 570

aircraft)

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

IATA (Passenger)

Packing instruction (passen: 570

ger aircraft)

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations:

Gefahrgruppe nach DGUV 13 Vorschrift 13 (bisher BGV B4): II (German regulatory requirements)

The components of this product are reported in the following inventories:

TCSI (TW) : On the inventory, or in compliance with the inventory

TSCA (US) : All substances listed as active on the TSCA inventory

AllC (AU) : On the inventory, or in compliance with the inventory

DSL (CA) : All components of this product are on the Canadian DSL

ENCS (JP) : On the inventory, or in compliance with the inventory

ISHL (JP) : On the inventory, or in compliance with the inventory

KECI (KR) : On the inventory, or in compliance with the inventory

PICCS (PH) : On the inventory, or in compliance with the inventory

IECSC (CN) : On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

This information is not available.

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

SECTION 16: Other information

Further information

Other information : This safety datasheet only contains information relating to

safety and does not replace any product information or prod-

uct specification.

These safety instructions also apply to empty packaging which

may still contain product residues.

Sources of key data used to

compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Classification of the mixture: Classification procedure:

Org. Perox. D H242 Based on product data or assessment

Eye Irrit. 2 H319 Calculation method Skin Sens. 1 H317 Calculation method Repr. 2 H361 Calculation method STOT SE 3 H335 Calculation method

Full text of H-Statements

H226 : Flammable liquid and vapour.
H242 : Heating may cause a fire.
H302 : Harmful if swallowed.
H311 : Toxic in contact with skin.

H317 : May cause an allergic skin reaction. H319 : Causes serious eye irritation.

H331 : Toxic if inhaled.

H335 : May cause respiratory irritation.

H361 : Suspected of damaging fertility or the unborn child.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Eye Irrit. : Eye irritation

Flam. Liq. : Flammable liquids

Org. Perox. : Organic peroxides

Repr. : Reproductive toxicity

Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure

ZA OEL : South Africa. Hazardous Chemical Substances Regulations,

Occupational Exposure Limits

ZA OEL / OEL-RL : Occupational Exposure Limit Restricted limit - 8- hour expo-

sure or equivalent (12 hour shifts)

ZA OEL / OEL- RL STEL/C : Occupational Exposure Limit Restricted limit - Short term oc-

NOROX®PD-40



Version Revision Date: SDS Number: Date of last issue: -

1.0 15.05.2023 60000000160 Date of first issue: 15.05.2023

cupational exposure limits / ceiling limits

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

ZA / EN