




FOGTAC

*Strong positioning spray adhesive
for Infusion & RTM*



DESCRIPTION

FOGTAC spray adhesive, designed to be used for vacuum infusion and RTM process, ensures perfect bonding of reinforcement layers during draping process.

It has a powerful bonding force, halfway between INFUTAC and MEGATAC.

With its mist effect, the evaporation of the solvents is facilitated and allows to obtain a quick tack on the surface of the reinforcements, while limiting the quantity deposited between the different layers.

FOGTAC adhesive does not interfere with resin flow, and therefore does not generate marking problems.

INSTRUCTIONS

Shake well before use. Application temperatures between 15°C and 40°C.

Ensure surface is clean, dry, and free of contamination.

Set the nozzle on L (Low) M (Middle) or H (High) to adjust the flow.

Spray a thin layer of adhesive on the surface to be bonded, at a distance of 15/20 cm.

Allow to dry (10 s) until a slightly viscous appearance is obtained. Apply the fabric to be bonded.

PROPERTIES

Colour	Spray pattern	Aerosol volume	Expiry date	Packaging	Flammability
Green	Fog	500 ml	18 months	Carboard box of 12 cans	Very flammable

The **FOGTAC** adhesive is compatible with most resins but remains under user validation.



COMPLY WITH CLP2015
REGULATION
applicable since 01/06/2015

**TOLUENE
FREE**

Ind A
Application date 01/2023